



Product description:

Iso Metal Primer WB is a water-soluble anti-corrosion primer based on a specially developed modified alkyd resin. The product also contains anti-corrosion pigments based on zinc phosphate and covering pigments.

Properties:

Thanks to its unique composition, Iso Metal Primer WB has the following properties:

- Good adhesion to steel, prepainted steel sheets, etc.
- Effective corrosion protection
- Fast drying
- Rapid achievement of water tightness – after about 4 hours' drying at 20° C
- Can be overpainted with water-based paints such as Isonit Tagmaling (all types and glosses) and solvent-based paints such as Iso Metal Top-coat.

Use:

Iso Metal Primer WB can be used on steel sheets and steel prepainted facade sheets (such as plastisol-coated sheets). The product can of course also be used to prime steel for general indoor and outdoor use.

Before applying Iso Metal Primer WB, the base should be cleaned thoroughly using a pressure washer to remove all dirt, grease, loose rust and paint.

During periods with low temperatures below 10-15° C, Iso Metal Primer SB no. 791-792 is recommended.

Technical Data:

Type:	Water-based modified alkyd
Colour:	Pale grey and Oxide red
Thinning:	If necessary with water, max. 5%
Coverage:	8-12 m ² /litre
Application method:	Brush, roller or spray
Coat thickness:	Recommended: Wet film 100 microns Dry film 40 microns
Gloss Value:	Approx. gloss 5 - matt
Specific Gravity:	Approx. 1.3 kg per litre
Drying Time:	Touch dry after about 1 hour at 20°C. Recoat after about 1-2 hours at 20°C. Lowest application and hardening temperature +10°C.
Storage:	Store dry and frost-free. Keep out of reach of children.
Paint code 93:	00 - 1



Tvaervej 6
6640 Lunderskov
Denmark
Tlf.: +45 7633 3114
Fax +45 7633 3115
E-mail: mail@isopaint.dk
www.isopaint.com

