



## Product Description:

Iso Metal Topcoat is a fast-drying, turpentine-soluble topcoat based on modified alkyd resin and light-fast pigments.

## Properties:

Thanks to its unique composition, Iso Metal Topcoat has the following properties:  
Robust, smooth surface which gives good weather resistance and oil- and water-resistance.

## Use:

Iso Metal Topcoat can be used on steel sheets and steel prepainted facade sheets (such as plastisol-coated sheets) which have been prepared using Iso Metal primer SB or Iso Metal primer WB. The product can of course also be used to paint primed steel for general indoor and outdoor use. Before applying Iso Metal Topcoat, the base should be cleaned thoroughly using a pressure washer to remove all dirt, grease, loose rust and paint.

## Technical Data:

<b>Type:</b>	Modified alkyd resin
<b>Colour:</b>	8 standard colours
<b>Gloss Value:</b>	Approx. 25%
<b>Thinning:</b>	If necessary with turpentine max. 20%
<b>Coverage:</b>	8-12 m <sup>2</sup> /litre
<b>Application method:</b>	Brush, roller or spray
<b>Coat thickness:</b>	Recommended: Wet film 100 microns Dry film 40 microns
<b>Specific Gravity:</b>	Approx. 1.3 kg per litre
<b>Drying Time:</b>	Touch dry after about 1 hour at 20° C. Recoat after about 4 hours at 20° C. Lowest application and hardening temperature +5° C.
<b>Storage:</b>	Store dry and frost-free. Keep out of reach of children.
<b>Paint code 93:</b>	2 - 1



Tvaervej 6  
6640 Lunderskov  
Denmark  
Tlf.: +45 7633 3114  
Fax +45 7633 3115  
E-mail: mail@isopaint.dk  
www.isopaint.com

