

# Iso Rubber Roof Paint

## Product description:



ISO Rubber roof painting is a special thick film painting, which has a massive rubber look consistence, when it is dry. To be used where the roof is either very damaged or leaky.

It has the ability to be put on in a very thick layer on almost every foundation like; asbestos cement, concrete, asphalt paper, tile, wood, cast, metal etc. It also contains parts against growth, and is added UV – absorbants

Furthermore the ISO Rubber Roof Paint is very elastic and can be stretched for 500-700 % the painting keeps its elasticity down to minus 20 °C



## Use:

ISO Rubber roof painting is applied on the clean surface with a brush, roller, or spray. It is important to apply plenty of paint, especially if the roof, is leaky or very damaged. If the foundation is very bad; it would

be of great advantage to use a net as foundation. This must be dipped in wet paint and applied 1 or 2 layers of ISO Rubber Painting. It is important to let the first layer dry completely before the next treatment.

You will achieve the best result by spraying.

## Technical Data:

<b>Colour:</b>	Black, anthracite grey, grey, tile red, red brown, mocca
<b>Dilute:</b>	If necessary with water
<b>Coverage:</b>	App. 3 m <sup>2</sup> per lt.
<b>Applications method:</b>	Brush, roller, or spray
<b>Gloss:</b>	App. 10
<b>Dry matter content:</b>	App. 65 w/w %
<b>Drying time:</b>	App. 1-2 hours at 20 °C, depending on the thickness of the painting, temperature, RH
<b>Second paint:</b>	Second painting/applying must not happen before the first applying has hardened after app.24 hours
<b>Storage:</b>	Dry, non-freezing, out of reach to children
<b>Cleaning:</b>	Tools etc. are cleaned in water

Tvaervej 6  
6640 Lunderskov  
Denmark  
Tlf.: +45 7633 3114  
Fax +45 7633 3115  
E-mail: mail@isopaint.dk  
www.isopaint.com



ISO PAINT NORDIC A/S