

HB 80 Finish High Gloss



Product description

HB 80 Finish High Gloss roof coating is used on asbestos cement and concrete roof tiles, where you wish a very exclusive look on the roof. The roof will be beautiful and shining and will also get extra good protection against growth of moss, algae and lichens.

Use



Before applying the roof coating the roof must be cleaned carefully with A-Clean. There must be no dirt, algae or moss. Apply the TG 80 Start Primer, which is a special coating in the same colour as the HB 80 Finish High Gloss coating, you want to apply.

The best result is achieved by spraying.

When the TG 80 Roof Primer has dried after app. 1-3 hours (depending on temperature and RH) HB 80 Finish Highgloss coating can be applied.

It is necessary to apply the HB 80 Finish High Gloss coating twice.

Please make a test to ensure compatability with the surface.

Technical data



Colour: Black, Bordeaux, mocca, tile red **Coverage:** App. 6 m²/l **Application**

method: Brush, roller or spray **Gloss:** App. gloss 80 **Dry matter content:**

App. 50 w/w % **Storage:** Dry, non-freezing, out of reach to children

Cleaning: Tools are cleaned in water **VOC:** 40 g/l /Cat A/c)

Benefits

Gives a very exclusive look

The roof will be beautiful and shining

Extra good protection against growth of moss, algae and lichens

Iso Paint Nordic A/S

Tvaervej 8
6640 Lunderskov
Denmark

Phone +45 7633 3114
Fax +45 7633 3115

mail@isopaint.com
www.isopaint.com



ISO PAINT NORDIC A/S