

ISO EPDM/TPO Cleaner



Preparation



Cleaner to be used in the treatment of EPDM or TPO.

Application



For exterior use only. Protective clothing eyewear should be used during application of this product. The surface must be free of loose dirt and growths. Apply the cleaner using a low pressure spray, roller or brush. Cover the entire surface starting at the highest point to make the residue of material run down to cover the uncleaned part of the roof. Do not allow residue to get on already cleaned surface as it will be necessary to clean it again. After applying the cleaner allow it to work for 15-20 minutes, then start power washing the surface in a cross hatch pattern. After cleaning wash with water and make sure no residues are left.

Recommendation: Always make a test to ensure the compatibility of product and surface.

Technical data



Composition: Liquid aqueous cleaning detergent. **Density:** 1,02 g/ml
pH: Approx. 11,7 **Dilution:** Ready for use **Application conditions:** The temperature must be 5°C - 35 °C **Application method:** Low pressure spray, roller or brush **Cleaning:** Water **Storage:** Cool, but free of frost in closed containers and out the reach of children.

Iso Paint Nordic A/S
Tvaervej 8
6640 Lunderskov
Denmark

Phone +45 7633 3114
Fax +45 7633 3115

mail@isopaint.com
www.isopaint.com



ISO PAINT NORDIC A/S