

ISO Façade Paint

Oil reinforced



Product description



ISO Façade Paint Oil Reinforced is a voluminous, breathable water-based façade paint that is reinforced with drying oils and added algaecides against surface fouling.

ISO Façade Paint Oil Reinforced has incredibly good adhesion even on poor surfaces with where, old paint and lime that has become attached.

ISO Façade Paint Oil Reinforced is composed of filling material and pigments so it decomposes very slowly, thus offering a self-cleaning surface.

When correctly applied on a suitable surface, ISO Façade Paint Oil Reinforced has a durability of up to 10 years outdoors.

Use



ISO Façade Paint Oil Reinforced is used indoors and outdoors as a façade paint on mineral surfaces such as concrete, plaster, brick, fibrous cement, cellular concrete, sand-lime brick, etc.

Used on top of both new and old painted surfaces with attached lime and paint. It is important that dirt, green fouling, loose flakes and fissures are thoroughly removed/stripped off before application using a stiff brush or low-pressure cleaner. Before application, the surface should be dry; we recommend initially to prime with ISO Façade Paint Oil Reinforced diluted with approx. 10 to 20% of water, especially where the surface is very dry and absorbent. For the best results, we recommend painting twice.

Recommendation: Always make a test coat to ensure the compatibility of product and surface.

Technical data



Structure: Water-based oil-reinforced façade paint with light-stable pigments and weather-stable, self-cleaning filling material. **Colours:** Sand, light slategrey, light grey, antrazit grey, mantion yellow, cream white, white.

Packaging: 20 litre. **Gloss:** Matt in gloss 5. **Drying time:** Approx. 1 – 2 hours at 20°C and 65 % RH, can be painted over after approx. 3 hours. **Application:** Brush, roller and paint spray gun (nozzle size 0.018 to 0.027"). **Volume dry matter:** Depending on colour and base, approx. 1.4 kg/litre. **Product VOC:** Maximum 38 g/litre. **Spreading capacity:** Approx. 4-6 m²/litre **Dilution:** Using ordinary water. **Cleaning:** Clean tools, etc in lukewarm soapy water.

Storage: Dry and frost-free, out of reach of children.

Benefits

Excellent good adhesion

Used indoors and outdoors

Durability up to 10 years outdoors when correctly applied on a suitable surface.



Iso Paint Nordic A/S
Tvaervej 8
6640 Lunderskov
Denmark

Phone +45 7633 3114
Fax +45 7633 3115

mail@isopaint.com
www.isopaint.com



ISO PAINT NORDIC A/S