

HB 80 Finish High Gloss



Product description



HB 80 Finish High Gloss roof coating is used on asbestos cement and concrete roof tiles, where you wish a very exclusive look on the roof. The roof will be beautiful and shining and will also get extra good protection against growth of moss, algae and lichens.

Use



Before applying the roof coating the roof must be cleaned carefully with A-Clean. There must be no dirt, algae or moss. Apply the TG 80 Start Primer, which is a special coating in the same colour as the HB 80 Finish High Gloss coating, you want to apply.

The best result is achieved by spraying.

When the TG 80 Roof Primer has dried after app. 1-3 hours (depending on temperature and RH) HB 80 Finish Highgloss coating can be applied.

It is necessary to apply the HB 80 Finish High Gloss coating twice.

Please make a test coat of the surface for controlling the capability.

Technical data



Colour: Black, Bordeaux, mocca, tile red **Coverage:** App. 6 m² per litre

Application method: Brush, roller, or spray **Gloss:** App. gloss 80

Dry matter content: App. 50 w/w % **Storage:** Dry, non-freezing, out of reach to children **Cleaning:** Tools are cleaned in water

Benefits

Gives very exclusive look

The roof will be beautiful and shining

Extra good protection against growth of moss, algae and lichens.



Iso Paint Nordic A/S
Tvaervej 8
6640 Lunderskov
Denmark

Phone +45 7633 3114
Fax +45 7633 3115

mail@isopaint.com
www.isopaint.com



DANAK
Quality &
Environmental system
according to
DS/EN ISO 9001
DS/EN ISO 14001
by
Det Norske Veritas,
Danmark A/S
Certification Dept.



ISO PAINT NORDIC A/S