

# StoneCleaner Extrem™

Universal cleaning product for mineral surfaces, etc.



## Product description:



Liquid, highly concentrated universal cleaning detergent with a high level of solubility on oils, grease, dirt and other forms of impurities on mineral surfaces of concrete, brick, etc.

Contains biodegradable anionic and non-ionic tensides, etc. carefully selected for effectiveness and for being gentle to the user and nature.

## Application:



Universal use for both manual and mechanical application as well as an additive in water through a high-pressure cleaner.

Used for cleaning mineral surfaces such as concrete, brick, etc., in public places, streets and pavements, industrial flooring, driveways and terraces with pavement blocks. Further uses include façade, tile roofs, concrete and fibre cement, while it can also be used on wooden surfaces.

After cleaning is complete, it is important that the cleaned surface is carefully washed with water by StoneCleaner to completely remove all residues.

If the surface is subsequently treated with an Iso product, such as Stone-Color, HydroBlock, ProCover or ConGuard, first make sure that the surface/coating is completely dry.

Before application, make an assessment of the condition of the surface to determine to what degree it is soiled/contaminated and use this as a base to select which the appropriate amount of dilution.

### Dosing:

In extreme cases, StoneCleaner Extrem can be used undiluted and be allowed to remain on the surface for a few minutes before commencing manual, mechanical rinsing with a water hose or cleaning with a high-pressure water cleaner.

However, under normal circumstances it can be used in concentrations of up to 1 part to 50 parts of water where it is still very effective.

**Please make a test coat of the surface for controlling the capability.**

## Technical data:



**Consistency:** Liquid aqueous universal cleaning detergent  
**Colour:** Natural/colourless **Smell:** Slightly soapy **Density:** Approx. 1.06 grams per ml. **PH:** Approx. 12.7 **Dilution:** From concentrated to diluted 1 part to 50 parts of water **Working temperature:** From 5°C to 35°C  
**Cleaning:** Working tools and high-pressure water jet machine should be thoroughly rinsed with water **Storage:** Store frost-free and out of reach of children

## Advantages

**A high level of solubility on oils, grease, dirt and other forms of dirt**

**Gentle for the user and nature.**

**Iso Paint Nordic A/S**  
Tvaervej 8  
6640 Lunderskov  
Denmark

Tlf. +45 7633 3114  
Fax +45 7633 3115

mail@isopaint.com  
www.isopaint.com



**DANAK**  
Quality &  
Environmental system  
according to  
DS/EN ISO 9001  
DS/EN ISO 14001  
by  
Det Norske Veritas,  
Danmark A/S  
Certification Dept.



**ISO PAINT NORDIC A/S**